

## TEI Lite



Encoding Content  
Manuscripts

## Gaps

- ⌘ `<gap>`
  - ☑ empty element
- ⌘ Attributes
  - ☑ desc
  - ☑ resp
- ⌘ `<gap desc='damage to corner of ms'>`

## Uncertain Reading

- ⌘ `<unclear>` element
  - ☑ `<unclear> ... </unclear>`
- ⌘ Attributes
  - ☑ reason
  - ☑ resp
  - ☑ `<unclear reason='fold in ms' resp='SM'> ... </unclear>`

## Deletions

- ⌘ `<del>` element
  - ☑ `<del> ... </del>`
- ⌘ Attributes
  - ☑ type
  - ☑ status
  - ☑ hand
- ⌘ `<del type='written over'> ... </del>`

## Additions

- ⌘ `<add>` element
  - ☑ `<add> ... </add>`
- ⌘ Attributes
  - ☑ place
  - ☑ hand
- ⌘ `<add hand='WW'> ... </add>`

## TEI Lite DTD

Creating Additional Entities

## Swash K

⌘ Often there is need to create entities to handle sorts used in letterpress editions for example terminal k as a swash sort

⌘ Lowercase swash k

⌘ User-defined

⌘ Example

```
<!ENTITY kswash CDATA "&kswash;" -- swash k -->
```

## Declaration

⌘ Where declared:

```
<!DOCTYPE tei.2 PUBLIC "-//TEI//DTD TEI Lite 1.6//EN" [  
  <!ENTITY kswash CDATA "&kswash;" -- swash k -->  
>  
<tei.2> ... </tei.2>
```